

| PIRANHA SHEARS | | | | | | | |
|---------------------------|----------------|---------------------------------|-------|---------------------------------|-------|---------------------------------|----------------------------------|
| MODEL | | 600 | | 800 | | 1000 | 1250 |
| | | 600-E | 600-D | 800-E | 800-D | | |
| SHEARING FORCE | tons | 600 | | 800 | | 1000 | 1250 |
| CLAMP FORCE | tons | 160 | | 160 | | 200 | 250 |
| FLIPPERS FORCE | tons | 2 x 120 | | 2 x 120 | | 2 x 150 | 2 x 150 |
| BLADE WIDTH | mm | 1020 | | 1020 | | 1020 | 1116 |
| DRIVING POWER | Electric (kW) | 2 x 55 | - | 2 x 75 | - | 2 x 90 | 3 x 90 |
| | Diesel (HP) | - | 200 | - | 350 | - | - |
| NUMBER OF CUTS PER MINUTE | 1 / Min. | 2 - 3 | | 2 - 3 | | 3 - 4 | 3 - 4 |
| PRODUCTION CAPACITY | tons / hour | 6 - 15 | | 15 - 30 | | 20 - 38 | 25 - 50 |
| FEEDING BOX DIMENSIONS | W x L (mm) | 2100 x 7000 | | 2100 x 7000 | | 2100 x 7000 | 2500 x 10000 |
| OVERALL DIMENSIONS | A x B x C (mm) | 3300 x 4000 x 9500 | | 3300 x 4000 x 9500 | | 3300 x 4000 x 9500 | 4250 x 6300 x 13500 |
| MAXIMUM CLAMP HEIGHT | mm | 995 / 1250 / 1500 / 1850 / 2200 | | 995 / 1250 / 1500 / 1850 / 2200 | | 995 / 1250 / 1500 / 1850 / 2200 | 1180 / 1525 / 1825 / 2275 / 2725 |
| MACHINE WEIGHT | tons | 55 | | 70 | | 100 | 160 |

Note: These data represent approximate values which are subject to change. Birim Makina has the right to change the data without prior notice. Number of cuts and production capacity are calculated for steel scrap and may differ due to material type and filling density in operation.

